

Digital Scanner DS 6608

Versatile Digital Scanner Future-Proofs Your Technology Investment

The DS 6608 Digital Scanner from Symbol Technologies, the Enterprise Mobility Company™, provides affordable, high-performance omnidirectional scanning of all major one-dimensional (1D) and two-dimensional (2D) bar code symbologies.

With powerful digital scanning features, the DS 6608 protects your IT investment by maximizing performance for today's applications and providing easy upgrade paths for future applications.

Innovations in Digital Scanning

User friendly for improved user productivity:

- ▶ Omnidirectional, point and shoot performance on 1D and 2D bar codes
- ▶ Five-Year Warranty
- ▶ Working range of 1-14 in./ 2.5–35.5cm on UPC/EAN symbols
- ▶ Intuitive laser generated aiming pattern
- ▶ Excellent performance on damaged or poorly printed bar codes

Cost-Effective Digital Scanning for Today's Applications

The DS 6608 Digital Scanner from Symbol Technologies is an excellent choice for your bar code scanning needs for capturing mission-critical information. The product's five-year warranty includes the exit window. In addition to advanced data capture technology, Symbol's end-to-end solutions integrate ruggedized mobile computers, wireless infrastructure, enabling software and high-ROI applications from our business partners. Symbol Enterprise Mobility Services ensure that your mobility solution works seamlessly and at maximum efficiency—from defining your business requirements through ongoing service and support.

For more information on the DS 6608 Digital Scanner, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at

www.symbol.com/ds6608



Features

Benefits

Omni-directional reading of 1D, 2D and Postal Codes	Greater productivity from one of the fastest hand-held digital scanners available
Widest working range available	Performs equally well from a distance or close-up, increasing productivity and user acceptance
Five-year warranty	Low total cost of ownership (TCO) – digital reliability
Multiple Interfaces out-of-the-box – On board	Change the host – keep the scanner
Intuitive, crisp aiming pattern	Quicker scans make the operators more productive and satisfied with the tool

DS 6608 Specification Highlights

Market: Point of Sale (POS)
Applications
1D bar codes
PDF 417 for age verification
User
Sales associate
Market: Postal
Applications
Check out
In-process operations
User
Sales Clerk
Warehouse clerk
Market: Lottery
Applications
Winning ticket verification
User
Sales Clerk
Market: Pharmacy
Applications
Reading RSS barcodes
User
Pharmacist/ Technician
Market: State and Local Government—Public safety
Applications
Citations
User
Police officer
Parking

Specifications are subject to change without notice. Symbol® is a registered trademark and The Enterprise Mobility Company™ is a trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners.

For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

Corporate Headquarters
Symbol Technologies, Inc.
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722.6234/+1.631.738.2400
FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
(Singapore Branch)
Asia Pacific Division
230 Victoria Street #05-07/09
Bugis Junction Office Tower
Singapore 188024
TEL: +65.6796.9600
FAX: +65.6337.6488

For Europe, Middle East and Africa
Symbol Technologies
EMEA Division
Symbol Place, Winnersh Triangle
Berkshire, England RG41 5TP
TEL: +44.118.9457000
FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
The Americas
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722.6234/+1.631.738.2400
FAX: +1.631.738.5990

Symbol Website
For a complete list of Symbol subsidiaries and business partners worldwide contact us at: www.symbol.com
Or contact our pre-sales team at:
www.symbol.com/sales




Physical Characteristics	
Dimensions:	6.55 in. H x 2.82 in. W x 4.72 in. D 16.64 cm H x 7.16 cm W x 11.99 cm
Weight (without cable):	6.04 oz./181.4 gm
Input Voltage:	5 volts +/- 10%
Operating Current:	250mA (average)
Power Sources:	Depending on host: • Host power • External power supply
Colors:	Cash Register White or Twilight Black
Performance Characteristics	
Light Source:	650 nm visible laser diode
Resolution:	640 x 480
Minimum Element Width:	5 mil/0.127 mm
Nominal Working Distance:	From 1 in./ 2.5 cm to 14 in. /35 cm on 100% UPC/EAN symbols
Print Contrast:	25% minimum reflective difference
Roll (Tilt): ¹	+/- 180 degrees from normal
Pitch: ²	+/- 60 degrees from normal
Skew (Yaw): ³	+/- 50 degrees from normal
Decode Capability:	
1-D Codes:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants
2-D Codes:	PDF417, microPDF417, MaxiCode, DataMatrix (ECC 2000), Composite Codes, QR Code
Postal Codes:	U.S. Postnet, U.S. Planet, U.K. Postal, Japan Postal, Australian Postal, Dutch Postal
Interfaces Supported:	RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse

User Environment	
Operating Temperature:	32° to 122° F/0° to 50° C
Storage Temperature:	-40° to 158° F/-40° to 70° C
Humidity:	5% to 95% relative humidity, noncondensing
Drop Specifications:	Unit functions normally after repeated 6 ft./1.8 m drops to concrete
Ambient Light Immunity:	Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight.
Sunlight:	10,000 ft. candles/107,644 LUX
Electrostatic Discharge:	Conforms to 15 kV air discharge and 8 kV of contact discharge


Accessories	
Hands-Free Intellistand™	20-66483-01, cash register white; 20-66483-02, twilight black
Regulatory	
Electrical Safety:	Certified to UL1950, CSA C22.2 No. 950, EN60950/IEC950
Laser Safety:	CDRH Class II, IEC Class 2
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA

Warranty	
The DS 6608 is warranted against defects in workmanship and materials for a period of 5 years (60 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty statement for details.	


- 1 - Roll (Tilt): Controlled by rotating the wrist clockwise or counterclockwise
2 - Pitch: Controlled by dropping or raising the wrist
3 - Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa



1D Decode Zone for DS 6608



2D Decode Zone for DS 6608



Part No. DS6608 Printed in USA 07/04 © Copyright 2004 Symbol Technologies, Inc.
All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply.

