



ZT610 and ZT620 Industrial Printer technical specifications

Specifications are provided for reference and are based on printer tests using Zebra Certified Supplies. Results may vary in actual application settings or when using other-than-recommended Zebra supplies. Zebra recommends always qualifying any application with thorough testing.



ZT610

Standard features

- Easy side-loading print mechanism
- Cableless quick change platen
- 4.3 in. color touch display with intuitive menu for quick operation and settings management
- Clear media side bi-fold door allows shorter media door opening radius, and easy monitoring of supplies usage without opening the printer
- Thin film printhead—with E3™ Element Energy™ Equalizer
- 1 GB SDRAM (32 MB User Available)
- 2 GB on board Flash memory (512 MB User Available)
- Cortex A9 800MHz Processor
- Serial RS-232, Full Speed (12 Mbps) USB 2.0, Bluetooth® 4.1, static NFC tag, and Auto-switching Gigabit Ethernet
- Two front mounted USB Host ports
- Dual media sensors—transmissive and reflective, selectable through software or front panel
- Real-time Clock (RTC)
- Energy Star® certified

Programming languages

- ZPL™ or ZPL II programming language—selectable through software or front panel
- XML-Enabled Printing—direct connect integration for barcode label printing; eliminates license fees and print server hardware and lowers customization and programming costs

Optional features

- Modular full-width guillotine style cutter with catch tray—operates under software control cutting labels individually or in strips (not compatible with rewind and peel options)
- Media rewind spindle—rewinds finished roll internally onto 3 in. (76 mm) core or enables label peel and liner rewind
- Ribbon Spindle—support for ribbon coated side in
- Applicator interface—provides status and control signals for applicators and remote control devices
- Additional fonts options
- RFID capabilities (UHF EPC Gen 2 V2.1/ISO 18000-63)
- Internal IPv4 10/100/1000 Wired Print Server Option Card
- IEEE 1284 Parallel Port
- External IPv6 Print Server (requires Parallel port option)
- Wireless dual radio 802.11ax Wi-Fi™ and Bluetooth 5.3

Printer operation

- Thermal transfer and direct thermal printing of barcodes, text and graphics
- Advanced label/media counters
- Auto calibration—printer calibrates when printer is turned on or when printhead is closed using approximately two labels

Zebra DNA™ for Printers

The ZT6 Series is powered by Link-OS™, Zebra's robust printer operating system, and Zebra DNA for Printers, a set of tools and applications designed to optimize your printers' performance over its entire lifecycle. The result is a superior printing experience through better performance, simplified remote manageability and easier integration. Please visit www.zebra.com/zebradna for more information.

Environmental specifications

- Operating environment:
 - Thermal transfer = 40°F to 104°F (5° to 40°C)
 - Direct thermal = 32°F to 104°F (0° to 40°C)
 - 20% to 85% non-condensing relative humidity
- Storage/transportation environment:
 - -22°F to 140°F (-30° to 60°C) 20% to 85% non-condensing relative humidity

Font specifications

- Fonts A, B, C, D, E, F, G, H and GS are expandable up to 10 times, height and width independently. However, fonts E and H (OCR-A and OCR-B) are not considered "in-spec" when expanded.
- The scalable smooth font O (CG Triumvirate™ Bold Condensed*) is expandable on a dot-by-dot basis, height and width independent, while maintaining smooth edges. Maximum character size depends on available memory.
- IBM Code Page 850 international character sets are available in the fonts A, B, C, D, E, F, G and O through software control
- Code Page 1250, 1252, 1253, 1254, 1255 Support with font O

Communications specifications

- USB 2.0, full-speed (12Mbps)
- RS-232 Serial (RS-232C with DB9F connector; Configurable baud rate (2400—115,200kB), parity, and data bits. Stop bits at 1 or 2; Software (XON/XOFF), hardware (DTR/DSR or RTS/CTS) communication handshake protocols)
- Gigabit internal Ethernet supports networks internally integrated option that enables the use of Webview and Alert features
- Bluetooth 4.1
- Dual front mounted (full-speed) USB Host ports

ZPL and ZPL II

- Communicates in printable ASCII characters
- Unicode™—Compliant
- Compatible with mainframe, mini and PC hosts
- Downloadable objects include graphics, scalable and bitmap fonts, label templates and formats
- Object copying between memory areas (RAM, Onboard Flash memory locations)
- Adjustable print cache
- Data compression
- Automatic memory allocation for format while printing
- Automatic serialization of fields
- Format inversion (white on black)
- Mirror-image printing
- Four position field rotation (0°, 90°, 180°, 270°)
- Slew command
- Programmable label quantities with print, pause, cut control
- User-programmable password
- Status messages to host on request

Barcode symbologies and specifications

- Barcode ratios: 2:1, 7:3, 5:2 and 3:1
- Linear barcodes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
- 2-dimensional barcodes: Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, TLC 39, MicroPDF, RSS-14 (and composite), Aztec

Physical specifications

Parameter	ZT610
Height	15.58 in. (395.7 mm)
Width	10.56 in. (262.2 mm)
Depth	19.88 in. (505 mm)
Weight	50 lbs./22.7 kg

Media specifications*

- Media type: continuous, die-cut, notch, hole, or black mark
- Media width (label and liner): 0.79 in. (20 mm) to 4.5 in. (114 mm)
- Minimum label length:
 - ZT610—203/300 DPI
 - Rewind mode: 0.25 in. (6 mm)
 - Peel mode: 0.5 in. (13 mm)
 - Tear-off mode: 0.7 in. (18 mm)
 - Cutter mode: 1.5 in. (38 mm)
 - ZT610—600 DPI
 - Rewind mode: 0.125 in. (3 mm)
 - Peel mode: 0.5 in. (13 mm)
 - Tear-off mode: 0.125 in. (3 mm)
 - Cutter mode: 1.5 in. (38 mm)
- Media thickness (label and liner): 0.003 in. (0.076 mm) to 0.012 in. (0.305 mm) non-cutter
- Maximum media roll size: 8.0 in. (203 mm) outside diameter on a 3 in. (76 mm) inside diameter core
 - Transmissive (gap) sensing standards:
 - Interlabel gap: 2–4 mm, preferably 3 mm
 - Sensing notch: 0.25 in. W (6 mm) × 0.12 in. L (3 mm)
 - Sensing hole: 0.125 in. (3 mm) diameter
 - Reflective (black mark) sensing standards:
 - Black mark length (parallel to inside media edge): 0.12 in.—0.43 in. (3–11 mm)
 - Black mark width (perpendicular to inside media edge): 0.43 in. (more than 11 mm)
 - Black mark location: within 0.040 in. (1 mm) of inside media edge
 - Black mark density: more than 1.0 Optical Density Units (ODU)
 - Maximum media density: 0.5 ODU

Ribbon specifications

- Standard lengths: 1476 ft. (450 m)
- Provides 3:1 media roll to ribbon ratios
- Maximum ribbon roll size:
 - 3.2 in. (81.3 mm) outside diameter on a 1.0 in. (25.4 mm) inside diameter core
- Ribbon wound coated-side out
- Ribbon width: 0.79 in. (20 mm) to 4.33 in. (110 mm)

Electrical specifications

- 250 watt rated Universal power supply with power-factor correction 90–265 VAC, 47–63 Hz
- Agency approvals: IEC 60950-1, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3
- Product Markings: cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark(Arg), CCC, GOST-R, BSMI, KCC, STB, and UkrSEPRO

* Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.

ZT610 203 DPI printing specifications

- 203 DPI resolution (8 dots/mm)
- Heater dimension (W × L): 0.0043 in. × 0.0052 in. (0.110 mm × 0.132 mm)
- First dot location measured from inside media edge: 0.14 in. ±0.05 in. (3.5 mm ±1.25 mm)
- Maximum print width: 4.09 in. (104 mm)
- Maximum non-continuous media print length 39 in. (991 mm)
- Maximum continuous media print length 150 in. (3810 mm)
- Programmable print speeds (in. per second): 2, 4, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14
- Barcode modulus "X" dimension:
 - Picket fence (non-rotated) orientation 4.9 mil to 49 mil
 - Ladder (rotated) orientation: 4.9 mil to 49 mil

Font specifications: 203 dpi (8 dots/mm)

Font	Matrix (H x W) in dots	Type*	Min. character size (H x W) in inches (mm)	Max. CPI
A	9 x 5	U-L-D	0.044 × 0.029 (1.1 × 0.74)	33.9
B	11 x 7	U	0.054 × 0.044 (1.37 × 1.1)	22.6
C, D	18 x 10	U-L-D	0.088 × 0.059 (2.2 × 1.5)	16.9
E	28 x 15	OCR-B	0.138 × 0.098 (3.5 × 2.5)	10.1
F	26 x 13	U-L-D	0.128 × 0.079 (3.3 × 2.0)	12.7
G	60 x 40	U-L-D	0.295 × 0.236 (7.5 × 6.0)	4.2
H	21 x 13	OCR-A	0.103 × 0.093 (2.6 × 2.4)	10.7
GS	24 x 24	SYMBOL	0.118 × 0.118 (3.0 × 3.0)	8.4
P	20 x 18	U-L-D	0.098 × 0.089 (2.50 × 2.25)	N/A
Q	28 x 24	U-L-D	0.138 × 0.113 (3.50 × 3.00)	N/A
R	35 x 31	U-L-D	0.172 × 0.153 (4.38 × 3.88)	N/A
S	40 x 35	U-L-D	0.197 × 0.172 (5.00 × 4.38)	N/A
T	48 x 42	U-L-D	0.236 × 0.207 (6.00 × 5.25)	N/A
U	59 x 53	U-L-D	0.290 × 0.261 (7.38 × 6.63)	N/A
V	80 x 71	U-L-D	0.394 × 0.349 (10.0 × 8.88)	N/A
Ø	variable	U-L-D	variable	N/A

*U—Uppercase L—Lowercase D—Descenders

ZT610 300 DPI printing specifications

- 300 DPI resolution (11.8 dots/mm)
- Heater dimension (W × L): 0.0027 in. × 0.0043 in. (0.0697 mm × 0.110 mm)
- First dot location measured from inside media edge: 0.08 in. ±0.05 in. (2.1 mm ±1.25 mm)
- Maximum print width: 4.09 in. (104 mm)
- Maximum non-continuous media print length: 39 in. (991 mm)
- Maximum continuous media print length: 100 in. (2540 mm)
- Programmable print speeds (in. per second): 2, 4, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12
- Barcode modulus "X" dimension:
 - Picket fence (non-rotated) orientation: 3.3 mil to 33 mil
 - Ladder (rotated) orientation: 3.9 mil to 39 mil

Font specifications: 300 dpi (12 dots/mm)

Font	Matrix (H x W) in dots	Type*	Min. character size (H x W) in inches (mm)	Max. CPI
A	9 x 5	U-L-D	0.030 × 0.020 (0.76 × 0.51)	50.0
B	11 x 7	U	0.037 × 0.030 (0.94 × 0.76)	33.3
C, D	18 x 10	U-L-D	0.060 × 0.040 (1.5 × 1.0)	25.0
E	28 x 15	OCR-B	0.137 × 0.087 (3.5 × 2.2)	11.5
F	26 x 13	U-L-D	0.087 × 0.053 (2.2 × 1.3)	18.8
G	60 x 40	U-L-D	0.200 × 0.160 (5.1 × 4.1)	6.3
H	21 x 13	OCR-A	0.100 × 0.093 (2.5 × 2.37)	10.7
GS	24 x 24	SYMBOL	0.080 × 0.080 (2.03 × 2.03)	12.5
P	20 x 18	U-L-D	0.067 × 0.060 (1.69 × 1.52)	N/A
Q	28 x 24	U-L-D	0.093 × 0.080 (2.37 × 2.03)	N/A
R	35 x 31	U-L-D	0.117 × 0.103 (2.96 × 2.62)	N/A
S	40 x 35	U-L-D	0.133 × 0.117 (3.39 × 2.96)	N/A
T	48 x 42	U-L-D	0.160 × 0.140 (4.06 × 3.56)	N/A
U	59 x 53	U-L-D	0.197 × 0.177 (5.00 × 4.49)	N/A
V	80 x 71	U-L-D	0.267 × 0.237 (6.77 × 6.01)	N/A
Ø	variable	U-L-D	variable	N/A

*U—Uppercase L—Lowercase D—Descenders

ZT610 600 DPI printing specifications

Standard ZT610 600 dpi; for 600 dpi Micro Label Printer specifications, see next page

- 600 DPI resolution (23.62 dots/mm)
- Heater dimension: Each heater consists of a split element. Each half being 13 microns (μm) $\times$ 70 microns (μm)
- First dot location measured from inside media edge: 0.08 in. $\pm$ 0.05 in. (2.1 mm $\pm$ 1.25 mm)
- Maximum print width: 4.09 in. (104 mm)
- Maximum non-continuous media print length: 39 in. (991 mm)
- Maximum continuous media print length: 30 in. (762 mm)
- Programmable print speeds (in. per second): 1, 2, 3, 4, 5, 6
- Barcode modulus "X" dimension:
 - Picket fence (non-rotated) orientation: 1.6 mil to 16 mil
 - Ladder (rotated) orientation: 1.6 mil to 16 mil

Font specifications: 600 dpi (24 dots/mm)

Font	Matrix (H x W) in dots	Type*	Min. character size (H x W) in inches (mm)	Max. CPI
A	9 x 5	U-L-D	0.015 x 0.010 (0.38 x 0.25)	100.0
B	11 x 7	U	0.018 x 0.015 (0.45 x 0.38)	66.7
C, D	18 x 10	U-L-D	0.030 x 0.020 (0.77 x 0.51)	50.0
E	28 x 15	OCR-B	0.137 x 0.087 (3.4 x 2.2)	11.54
F	26 x 13	U-L-D	0.043 x 0.027 (1.1 x 0.69)	37.5
G	60 x 40	U-L-D	0.100 x 0.080 (2.5 x 2.0)	12.5
H	21 x 13	OCR-A	0.100 x 0.093 (2.5 x 2.4)	10.71
GS	24 x 24	SYMBOL	0.040 x 0.040 (1.0 x 1.0)	25.0
P	20 x 18	U-L-D	0.033 x 0.030 (0.85 x 0.77)	N/A
Q	28 x 24	U-L-D	0.047 x 0.040 (1.19 x 1.02)	N/A
R	35 x 31	U-L-D	0.059 x 0.052 (1.49 x 1.32)	N/A
S	40 x 35	U-L-D	0.067 x 0.059 (1.70 x 1.49)	N/A
T	48 x 42	U-L-D	0.080 x 0.070 (2.04 x 1.79)	N/A
U	59 x 53	U-L-D	0.099 x 0.089 (2.51 x 2.25)	N/A
V	80 x 71	U-L-D	0.134 x 0.199 (3.40 x 5.06)	N/A
Ø	variable	U-L-D	variable	N/A

*U—Uppercase L—Lowercase D—Descenders

ZT610 600 DPI Micro Label Printer

Additional features

In addition to the features on a standard ZT610, the ZT610 600 dpi Micro Label Printer includes:

- Additional front sensor to accurately detect micro label position and ensure precise alignment
 - Peel sensor mechanism to support peeling labels as small as 6 mm
 - Media holder and extending media guide to support very narrow media rolls
 - Extended tear bar to improve the position of the label output for automated labeling systems
 - Precision Printing Mode
-

Optional features

- Rewind: can be operated in rewind mode to internally rewind a full roll of printed labels or peel mode to peel label and rewind liner: can be operated in rewind mode to internally rewind a full roll of printed labels or peel mode to peel label and rewind liner
- Two open communication slots to add internal cards for:
 - Dual band 802.11ax Wi-Fi and Bluetooth 5.3
 - Parallel
 - Ethernet
 - Applicator interface

Note: Cutter and RFID are not supported on the ZT610 600 dpi Micro Label Printer

ZT610 600 DPI Micro Label printing specifications

- 600 DPI resolution (23.62 dots/mm)
- Heater dimension: Each heater consists of a split element. Each half being 13 microns (μm) $\times$ 70 microns (μm)
- First dot location measured from inside media edge: 0.08 in. $\pm$ 0.05 in. (2.1 mm $\pm$ 1.25 mm)
- Maximum print width: 4.09 in. (104 mm)
- Maximum non-continuous media print length: 39 in. (991 mm)
- Maximum continuous media print length: 30 in. (762 mm)
- Media registration tolerance*:
 - Vertical:
 - » Up to $\pm$ 0.35 mm at print speeds at or below 2 ips in tear or peel mode
 - » Up to $\pm$ 0.45 mm at print speeds at or below 2 ips in batch or rewind mode
 - » Up to $\pm$ 0.45 mm at print speeds 3 to 6 ips in tear or peel mode
 - » Up to $\pm$ 0.45 mm at print speeds 3 to 6 ips in batch or rewind mode
 - Horizontal:
 - » $\pm$ 0.5 mm at print speeds at or below 2 ips
 - » $\pm$ 0.75 mm at print speeds 3 to 6 ips
- Programmable print speeds (in. per second): 1, 2, 3, 4, 5, 6
- Barcode modulus "X" dimension:
 - Picket fence (non-rotated) orientation: 1.6 mil to 16 mil
 - Ladder (rotated) orientation: 1.6 mil to 16 mil

*Specifications are provided for reference and are based on printer tests using Zebra Certified Supplies. Results may vary in actual application settings or when using other-than-recommended Zebra supplies. Minimum print registration can vary based on media type and size. Zebra recommends always qualifying any application with thorough testing.

Media and ribbon specifications¹

- Media type: continuous, die-cut, notch, hole, or black mark
- Media width (label and liner): 0.47 in. (12 mm) to 4.5 in. (114 mm)
- Minimum label length:
 - » Rewind mode: 0.12 in. (3 mm)
 - » Peel mode: 0.24 in. (6 mm)
 - » Tear-off mode: 0.12 in. (3 mm)
 - » Cutter mode: 1.5 in. (38 mm)
- Ribbon width:
 - 0.79 in. (20 mm) to 4.33 in. (110 mm)

For standard ZT610 600 dpi, see page 3.

¹ Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.

Font specifications: 600 dpi (24 dots/mm)

Font	Matrix (H x W) in dots	Type*	Min. character size (H x W) in inches (mm)	Max. CPI
A	9 x 5	U-L-D	0.015 x 0.010 (0.38 x 0.25)	100.0
B	11 x 7	U	0.018 x 0.015 (0.45 x 0.38)	66.7
C, D	18 x 10	U-L-D	0.030 x 0.020 (0.77 x 0.51)	50.0
E	28 x 15	OCR-B	0.137 x 0.087 (3.4 x 2.2)	11.54
F	26 x 13	U-L-D	0.043 x 0.027 (1.1 x 0.69)	37.5
G	60 x 40	U-L-D	0.100 x 0.080 (2.5 x 2.0)	12.5
H	21 x 13	OCR-A	0.100 x 0.093 (2.5 x 2.4)	10.71
GS	24 x 24	SYMBOL	0.040 x 0.040 (1.0 x 1.0)	25.0
P	20 x 18	U-L-D	0.033 x 0.030 (0.85 x 0.77)	N/A
Q	28 x 24	U-L-D	0.047 x 0.040 (1.19 x 1.02)	N/A
R	35 x 31	U-L-D	0.059 x 0.052 (1.49 x 1.32)	N/A
S	40 x 35	U-L-D	0.067 x 0.059 (1.70 x 1.49)	N/A
T	48 x 42	U-L-D	0.080 x 0.070 (2.04 x 1.79)	N/A
U	59 x 53	U-L-D	0.099 x 0.089 (2.51 x 2.25)	N/A
V	80 x 71	U-L-D	0.134 x 0.199 (3.40 x 5.06)	N/A
Ø	variable	U-L-D	variable	N/A

*U—Uppercase L—Lowercase D—Descenders

ZT620

Physical specifications

Parameter	ZT620
Height	15.58 in. H (395.7 mm)
Width	13.44 in. (341.5 mm)
Depth	19.88 in. (505 mm)
Weight	57.4 lbs./26 kg

Media specifications*

- Media type: continuous, die-cut, notch, hole, or black mark
- Minimum label length:
 - Rewind mode: 0.25 in. (6 mm)
 - Peel mode: 0.5 in. (13 mm)
 - Tear-off mode: 0.7 in. (18 mm)
 - Cutter mode: 1.5 in. (38 mm)
- Media thickness (label and liner):
 - 0.003 in. (0.076 mm) to 0.007 in. (0.18 mm) cutter
 - 0.003 in. (0.076 mm) to 0.012 in. (0.305 mm)
- Maximum media roll size:
 - 8.0 in. (203 mm) outside diameter on a 3 in. (76 mm) inside diameter core
- Transmissive (gap) sensing standards:
 - Interlabel gap: 2–4 mm, preferably 3 mm
 - Sensing notch: 0.25 in. W (6 mm) × 0.12 in. L (3 mm)
 - Sensing hole: 0.125 in. (3 mm) diameter
- Reflective (black mark) sensing standards:
 - Black mark length (parallel to inside media edge): 0.12 in.–0.43 in. (3–11 mm)
 - Black mark width (perpendicular to inside media edge): 0.43 in. (more than 11 mm)
 - Black mark location: within 0.040 in. (1 mm) of inside media edge
 - Black mark density: more than 1.0 Optical Density Units (ODU)
 - Maximum media density: 0.5 ODU
- Media width (label and liner): 2.0 in. (51 mm) to 7.1 in. (180 mm)

Ribbon specifications

- Standard lengths: 1476 ft. (450 m)
- Provides 3:1 media roll to ribbon ratios
- Maximum ribbon roll size: 3.2 in. (81.3 mm) outside diameter on a 1.0 in. (25.4 mm) inside diameter core
- Ribbon wound coated-side out
- Ribbon width: 2.0 in. (51 mm) to 6.7 in. (170 mm)

Electrical specifications

- 250 watt rated Universal power supply with power-factor correction 90–265 VAC, 47–63 Hz
- Agency approvals: IEC 60950-1, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3
- Product Markings: cTUVus, CE, FCC-B, ICES- 003, VCCI, C-Tick, NOM, S-Mark(Arg), CCC, GOST-R, BSMI, KCC, STB, and UkrSEPRO

* Media registration and minimum label length are affected by media type and width, ribbon type, and print speed. Performance improves as these factors are optimized. Zebra recommends always qualifying any application with thorough testing.

ZT620 203 DPI printing specifications

- 203 DPI resolution (8 dots/mm)
- Heater Dimension: 0.0043 in. x 0.0052 in. (0.110 mm x 0.132mm)
- First dot location measured from inside media edge: -0.10 in. $\pm$ 0.035 in. (2.5mm $\pm$ 0.9 mm)
- Maximum print width: 6.6 in. (168 mm)
- Maximum non-continuous media print length: 39 in. (991 mm)
- Maximum continuous media print length 80 in. (2032 mm)
- Programmable print speeds (in. per second): 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12
- Barcode modulus "X" dimension:
 - Picket fence (non-rotated) orientation: 4.9 mil to 49 mil
 - Ladder (rotated) orientation: 4.0 mil to 40 mil

Font specifications: 203 dpi (8 dots/mm)

Font	Matrix (H x W) in dots	Type*	Min. character size (H x W) in inches (mm)	Max. CPI
A	9 x 5	U-L-D	0.044 x 0.029 (1.1 x 0.74)	33.9
B	11 x 7	U	0.054 x 0.044 (1.37 x 1.1)	22.6
C, D	18 x 10	U-L-D	0.088 x 0.059 (2.2 x 1.5)	16.9
E	28 x 15	OCR-B	0.138 x 0.098 (3.5 x 2.5)	10.1
F	26 x 13	U-L-D	0.128 x 0.079 (3.3 x 2.0)	12.7
G	60 x 40	U-L-D	0.295 x 0.236 (7.5 x 6.0)	4.2
H	21 x 13	OCR-A	0.103 x 0.093 (2.6 x 2.4)	10.7
GS	24 x 24	SYMBOL	0.118 x 0.118 (3.0 x 3.0)	8.4
P	20 x 18	U-L-D	0.098 x 0.089 (2.50 x 2.25)	N/A
Q	28 x 24	U-L-D	0.138 x 0.113 (3.50 x 3.00)	N/A
R	35 x 31	U-L-D	0.172 x 0.153 (4.38 x 3.88)	N/A
S	40 x 35	U-L-D	0.197 x 0.172 (5.00 x 4.38)	N/A
T	48 x 42	U-L-D	0.236 x 0.207 (6.00 x 5.25)	N/A
U	59 x 53	U-L-D	0.290 x 0.261 (7.38 x 6.63)	N/A
V	80 x 71	U-L-D	0.394 x 0.349 (10.0 x 8.88)	N/A
Ø	variable	U-L-D	variable	N/A

*U—Uppercase L—Lowercase D—Descenders

ZT620 300 DPI printing specifications

- 300 DPI resolution (11.8 dots/mm)
- Heater dimension (W × L): 0.0027 in. × 0.0043 in. (0.0697 mm × 0.110 mm)
- First dot location measured from inside media edge:
 - -0.10 in. ±0.035 in. (2.5mm ±0.9 mm)
- Maximum print width: 6.6 in. (168 mm)
- Maximum non-continuous media print length: 39 in. (991 mm)
- Maximum continuous media print length 80 in. (2032 mm)


Font specifications: 300 dpi (12 dots/mm)

Font	Matrix (H x W) in dots	Type*	Min. character size (H x W) in inches (mm)	Max. CPI
A	9 x 5	U-L-D	0.030 × 0.020 (0.76 × 0.51)	50.0
B	11 x 7	U	0.037 × 0.030 (0.94 × 0.76)	33.3
C, D	18 x 10	U-L-D	0.060 × 0.040 (1.5 × 1.0)	25.0
E	28 x 15	OCR-B	0.137 × 0.087 (3.5 × 2.2)	11.5
F	26 x 13	U-L-D	0.087 × 0.053 (2.2 × 1.3)	18.8
G	60 x 40	U-L-D	0.200 × 0.160 (5.1 × 4.1)	6.3
H	21 x 13	OCR-A	0.100 × 0.093 (2.5 × 2.37)	10.7
GS	24 x 24	SYMBOL	0.080 × 0.080 (2.03 × 2.03)	12.5
P	20 × 18	U-L-D	0.067 × 0.060 (1.69 × 1.52)	N/A
Q	28 × 24	U-L-D	0.093 × 0.080 (2.37 × 2.03)	N/A
R	35 × 31	U-L-D	0.117 × 0.103 (2.96 × 2.62)	N/A
S	40 × 35	U-L-D	0.133 × 0.117 (3.39 × 2.96)	N/A
T	48 × 42	U-L-D	0.160 × 0.140 (4.06 × 3.56)	N/A
U	59 × 53	U-L-D	0.197 × 0.177 (5.00 × 4.49)	N/A
V	80 × 71	U-L-D	0.267 × 0.237 (6.77 × 6.01)	N/A
Ø	variable	U-L-D	variable	N/A

*U—Uppercase L—Lowercase D—Descenders

Need more information?

You'll find additional resources and support at www.zebra.com/zt600



The Zebra wordmark and logo are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. The Bluetooth® wordmark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Zebra is under license. Wi-Fi™ is a trademark of Wi-Fi Alliance®. All other trademarks are the property of their respective owners. ©2026 Zebra Technologies Corp. and/or its affiliates. 03/27/2026.

zebracod.ir